

Rely on
WITT for gas safety
technology.



HOW IMPORTANT IS SAFE GAS SUPPLY?

ANDREAS HEYER: SENIOR PRODUCT MANAGER – WITT-GASETECHNIK


CENTRAL GAS SUPPLY SYSTEMS INCREASE SAFETY AND PRODUCTIVITY!


Continuous gas supply, improved safety by less transportation of gas cylinders, more space at the point of use, flexibility and expandability – central gas supply systems offer numerous benefits. Field-proven solutions by WITT ensure the optimal realisation from gas inlet to outlet point, from conception to implementation.

As market leader with longtime experience WITT offers all components for central gas supply systems – gas mixers, pressure regulator stations, flashback arrestors, outlet points, electronic control and special equipment. Complete systems by WITT meet the most challenging requirements ensuring best quality, high flow rates and minimum pressure loss.

Our BAM-tested and certified products set standards. Rely on German quality and contact persons globally.

WITT – CENTRAL GAS SUPPLY SYSTEMS FROM A SINGLE SOURCE!





1 > FLASHBACK ARRESTORS

1A For regulators, outlet points, pipelines

1B For hoses

1C For torches

1D For cutting machines

2 > PRESSURE REGULATOR STATIONS AND OUTLET POINTS

2A Dome pressure regulators

2B Pressure regulator stations

2C Outlet points

2D Electronic switch and control

3 > NON-RETURN VALVES

4 > SAFETY RELIEF VALVES

5 > QUICK COUPLINGS
(for outlet points, pipelines, torches)

6 > GAS FILTERS

7 > GAS MIXERS

8 > SPECIAL EQUIPMENT

8A Decomposition Arrestors


8B Automatic slam shut valves

8C Ball valves

8D Safety hose reels

8E Test equipment


PRODUCT PORTFOLIO



1 FLASHBACK ARRESTORS

Protection of single cylinders, outlet points or pipelines against reverse gas flow and flashbacks:

- Combination of all safety elements for optimal protection
- Extinguish dangerous flashbacks or backfire
- Avoid explosive mixtures in the gas supply
- Wide product range for all kinds of applications
- For all technical gases
- Installation independent of the orientation
- Long service life due to protection against dirt – via filter at gas inlet
- All connections available
- Available in brass or stainless steel



3 NON-RETURN VALVES

Protection of equipment, pipelines and outlet points against reverse gas flow:

- Avoid the formation of explosive mixtures in the gas supply
- Varying from 3 mbarg–300 barg and flows between 0.01 m³/h–26,800 m³/h with any wanted connection
- For all technical gases – wide range of applications
- Low pressure drops – using complex valve assembly with low opening pressures
- No leaks – using of a spring loaded valve assembly with elastomer sealing
- Installation independent of the orientation
- All connections available
- Available in brass or stainless steel



2 PRESSURE REGULATORS

Constant gas flow and control of central gas supplies:


- Continuous gas supply and control of a pipeline
- With manual or automatic change-over
- Completely mounted and tested
- Compact design
- Reduces the risk of accidents



4 SAFETY RELIEF VALVES

Avoiding over-pressure by gas blowdown from pipelines and other equipment:


- Venting of excess pressure to protect down-stream equipment
- Individual opening pressure from 5 mbarg to 45 barg
- Compact size
- Installation independent of the orientation
- Protective dust cap
- Range of inlet connections
- Available in brass or stainless steel
- Also as a smart valve with visual indication of the status and digital signal for transmission to a network



5 QUICK COUPLINGS

Safe and quick connection of equipment:

- Lightning fast connection and disconnection of equipment
- Gas-tightness when disconnected
- No build-up of explosive gas-mixtures in the pipe line – because of non-return valve
- No confusion between connections – because of different probes for Oxygen, Fuel and Inert Gases
- Simplest selection of the right body and probe – because of new colour coded probe
- All connections available
- Dirt-filter protects hose coupling and equipment



6 GAS FILTERS

Reliable filtration of the finest dirt particles in gases:


- For pipelines and gas outlet points.
Some with condensation outlet
- For particles from 0.5–80 micron
- Diverse applications – useful for many technical gases
- High flow rates
- Extend the service life of downstream equipment – by reliable filtration performance
- Change of filter possible while installed
- Large choice of connections



7 GAS MIXERS

High quality mixing systems for 2 or 3 gases particularly for all areas with sharply fluctuating mixed gas flows:

- Easy operation
- A proportional mixing valve or three single mixing valves provide infinitely variable mixture settings
- Gas mixture withdrawal possible from zero to the maximum flow capacity
- High process reliability
- Independent of pressure fluctuations in the gas supply
- Intermittent gas mixture withdrawal possible
- Splash-proof and robust stainless steel housing
- For flammable gases available as EEx-version with separate control cabinet
- Integrated gas analysis for the control and documentation of the gas mixture production
- Monitoring of the gas supply with alarm











8 TEST EQUIPMENT






For the testing of all safety elements including flashback arrestors and non-return valves.

- Cost effective
- Only one test rig for all tests
 - Leak tightness to atmosphere
 - Test of non-return valve against low and high back pressure
 - Function of pressure sensitive gas cut off valve
 - Measurement of flow capacity of safety device
- Clear readings
- Robust design
- Maintenance free


Material	Image	Model	Remarks	Gases / Max. working pressures / Flows					Safety elements					
				Acetylene (A)	Oxygen (O ₂)	LPG (P)	Hydrogen (H ₂)	Natural Gas (M)	Inlet Gas Filter – depending on connection	Flame Arrestor (FA)	Non-Return Valve (NV)	Temperature activated Cut-off Valve (TV)	Pressure actuated Cut-off Valve (PV)	Pressure Relief Valve
Brass		RF53N		1,5 barg / 13 m ³ /h	25 barg	5 barg	3 barg	5 barg	X	X	X	X		
		RF53DN		1,5 barg / 11,5 m ³ /h	10 barg	5 barg	3 barg	5 barg	X	X	X	X		X
		RF53NSK	quick connect (ISO 7289)	1,5 barg / 13 m ³ /h	20 barg	5 barg	3 barg	5 barg	X	X	X	X		
		85-10		1,5 barg / 22 m ³ /h	25 barg	5 barg	4 barg	5 barg	X	X	X	X		
		85-20		2 barg / 45 m ³ /h	16 barg	4 barg	4 barg	4 barg	X	X	X	X		
		85-30		1,5 barg / 70 m ³ /h	25 barg	3,5 barg	4 barg	5 barg	X	X	X	X		
Nickel-plated		RF53N-ES		1,5 barg / 13 m ³ /h	25 barg	5 barg	3 barg	5 barg	X	X	X	X		
		RF53N/H-ES				8 barg	10 barg	12 barg	X	X	X	X		
		RF85-10N-ES		1,5 barg / 22 m ³ /h	25 barg	5 barg	4 barg	5 barg	X	X	X	X		








Material		Model	Remarks	Gases / Max. working pressures / Flows					Safety elements				
				Acetylene (A)	Oxygen (O ₂)	LPG (P)	Hydrogen (H ₂)	Natural Gas (M)	Inlet Gas Filter – depending on connection	Flame Arrestor (FA)	Non-Return Valve (NV)	Temperature activated Cut-off Valve (TV)	Pressure actuated Cut-off Valve (PV)
Nickel-plated		RF85-10N/H-ES				5 barg	10 barg	10 barg	X	X	X	X	
		RF85-20N-ES		2 barg / 45 m ³ /h	16 barg	4 barg	4 barg	4 barg	X	X	X	X	
		RF85-30N-ES		1,5 barg / 70 m ³ /h	25 barg	3,5 barg	4 barg	5 barg	X	X	X	X	
		RF 85-30N/H-ES				5 barg	11 barg	8 barg	X	X	X	X	
		F100N-ES						17 barg		X		X	
Messing		Super 55	resettable only PV	1,5 barg / 10 m ³ /h	15 barg	5 barg	3 barg	5 barg	X	X	X	X	
		Super 90	resettable only PV	1,5 barg / 11 m ³ /h	10 barg	4 barg	5 barg	5 barg	X	X	X	X	X
		Super 78	resettable only PV	1,5 barg / 11 m ³ /h	10 barg	4 barg	5 barg	5 barg	X	X	X	X	X





1 > **FLASHBACK ARRESTORS** | for regulators, outlet points, pipelines, DIN EN ISO 5175-1

Material	Image	Model	Remarks	Gases / Max. working pressures / Flows					Safety elements					
				Acetylene (A)	Oxygen (O ₂)	LPG (P)	Hydrogen (H ₂)	Natural Gas (M)	Inlet Gas Filter – depending on connection	Flame Arrestor (FA)	Non-Return Valve (NV)	Temperature activated Cut-off Valve (TV)	Pressure activated Cut-off Valve (PV)	Pressure Relief Valve
Brass		Super 66	resettable	2 barg / 20 m ³ /h	10 barg	5 barg	5 barg	5 barg	X	X	X	X	X	
		RF53N/30				3 barg		4 barg	X	X	X	X		
		85-10N/30				1,5 barg	0,2 barg	1,5 barg	X	X	X	X		
		270N 270 NU				2 barg	1,5 barg	3 barg		X	X	X		
		623N 623 NU				2 barg	1,5 barg	3,5 barg		X	X	X		

1 > **FLASHBACK ARRESTORS** | for hoses









Brass		E460-2	hose nipple	1,5 barg / 9 m ³ /h	20 barg	5 barg	4 barg	5 barg	X	X	X		
-------	---	--------	-------------	--------------------------------	---------	--------	--------	--------	---	---	---	--	--

Material	Model	Remarks	Gases / Max. working pressures / Flows					Safety elements						
			Acetylene (A)	Oxygen (O ₂)	LPG (P)	Hydrogen (H ₂)	Natural Gas (M)	Inlet Gas Filter – depending on connection	Flame Arrestor (FA)	Non-Return Valve (NV)	Temperature activated Cut-off Valve (TV)	Pressure activated Cut-off Valve (PV)	Pressure Relief Valve	
Brass		E460-1	hose nipple	1,5 barg / 9 m ³ /h	20 barg	5 barg	4 barg	5 barg	X	X	X			
		E460-3		1,5 barg / 9 m ³ /h	20 barg	5 barg	4 barg	5 barg	X	X	X			
		E460SK	quick connect (ISO 7289)	1,5 barg / 9 m ³ /h	20 barg	5 barg	4 barg	5 barg	X	X	X			
		E460SKU	quick connect (ISO 7289)	1,5 barg / 13 m ³ /h	20 barg	5 barg	4 barg	5 barg		X	X			
		RF53NU		1,5 barg / 13 m ³ /h	25 barg	5 barg	3 barg	5 barg	X	X	X	X		
		85-10NU		1,5 barg / 22 m ³ /h	25 barg	5 barg	4 barg	5 barg	X	X	X	X		
		85-10NU (Exzenter)	off-centre-nut	1,5 barg / 22 m ³ /h	25 barg	5 barg	4 barg	5 barg	X	X	X	X		



Material	Model	Remarks	Gases / Max. working pressures / Flows					Safety elements						
			Acetylene (A)	Oxygen (O ₂)	LPG (P)	Hydrogen (H ₂)	Natural Gas (M)	Inlet Gas Filter – depending on connection	Flame Arrestor (FA)	Non-Return Valve (NV)	Temperature activated Cut-off Valve (TV)	Pressure activated Cut-off Valve (PV)	Pressure Relief Valve	
Brass		E460-3		1,5 barg / 9 m ³ /h	20 barg	5 barg	4 barg	5 barg	X	X	X			
		RF53U		1,5 barg / 13 m ³ /h	25 barg	5 barg	2 barg	5 barg	X	X	X			
		85-10U		1,5 barg / 22 m ³ /h	25 barg	5 barg	4 barg	5 barg	X	X	X			
		85-10NU (Excenter)	off-centre-nut	1,5 barg / 22 m ³ /h	25 barg	5 barg	4 barg	5 barg	X	X	X			

MORE SAFETY IS NOT POSSIBLE










Application	Model	Remarks	Gases / Max. working pressures / Flows								
			Acetylene (A)	Oxygen (O ₂)	LPG (P)	Hydrogen (H ₂)	Natural Gas (M)	Argon (Ar)	Nitrogen (N ₂)		
Dome pressure regulator		737LE-HD/S	Set including Pilot pressure regulator, inlet and back pressure gauge, connections up to G3", flange DN80/100		Max. inlet pressure 200 barg Outlet pressure 0,5-60 barg Kv-Value = 1,65	Max. inlet pressure 100 barg Outlet pressure 0,5-60 barg Kv-Value = 1,65	Max. inlet pressure 300 barg Outlet pressure 0,5-60 barg Kv-Value = 1,65	Max. inlet pressure 300 barg Outlet pressure 0,5-60 barg Kv-Value = 1,65	Max. inlet pressure 300 barg Outlet pressure 0,5-60 barg Kv-Value = 1,65	Max. inlet pressure 300 barg Outlet pressure 0,5-60 barg Kv-Value = 1,65	
		737LE/S			Max. inlet pressure 30 barg Outlet pressure 0,5-29 barg Kv-Value = 2,4 / 3,6 / 15 / 30	Max. inlet pressure 25 barg Outlet pressure 0,5-16 barg Kv-Value = 2,4 / 3,6 / 15 / 30	Max. inlet pressure 40 barg Outlet pressure 0,5-30 barg Kv-Value = 2,4 / 3,6 / 15 / 30	Max. inlet pressure 40 barg Outlet pressure 0,5-29 barg Kv-Value = 2,4 / 3,6 / 15 / 30	Max. inlet pressure 40 barg Outlet pressure 0,5-30 barg Kv-Value = 2,4 / 3,6 / 15 / 30	Max. inlet pressure 40 barg Outlet pressure 0,5-30 barg Kv-Value = 2,4 / 3,6 / 15 / 30	
		747LE/S									
		757LE/S									
		767LE/S									
		Smart Version Modell 747/757/767			Max. inlet pressure 30 barg Outlet pressure 0,5-29 barg Kv-Value = 3,6 / 15 / 30	Max. inlet pressure 25 barg Outlet pressure 0,5-16 barg Kv-Value = 3,6 / 15 / 30	Max. inlet pressure 40 barg Outlet pressure 0,5-30 barg Kv-Value = 3,6 / 15 / 30	Max. inlet pressure 40 barg Outlet pressure 0,5-30 barg Kv-Value = 3,6 / 15 / 30	Max. inlet pressure 40 barg Outlet pressure 0,5-30 barg Kv-Value = 3,6 / 15 / 30	Max. inlet pressure 40 barg Outlet pressure 0,5-30 barg Kv-Value = 3,6 / 15 / 30	
		737LE-HD/S-ES	Set including Pilot pressure regulator, inlet and back pressure gauge, connections up to G3", flange DN80/100		Max. inlet pressure 30 barg Outlet pressure 0,5-29 barg Kv-Value = 1,65	Max. inlet pressure 100 barg Outlet pressure 0,5-26 barg Kv-Value = 1,65	Max. inlet pressure 300 barg Outlet pressure 0,5-60 barg Kv-Value = 1,65	Max. inlet pressure 300 barg Outlet pressure 0,5-60 barg Kv-Value = 1,65	Max. inlet pressure 300 barg Outlet pressure 0,5-60 barg Kv-Value = 1,65	Max. inlet pressure 300 barg Outlet pressure 0,5-60 barg Kv-Value = 1,65	
		737LE/S-ES			Max. inlet pressure 30 barg Outlet pressure 0,5-29 barg Kv-Value = 2,4 / 3,6 / 15 / 30	Max. inlet pressure 25 barg Outlet pressure 0,5-16 barg Kv-Value = 2,4 / 3,6 / 15 / 30	Max. inlet pressure 40 barg Outlet pressure 0,5-30 barg Kv-Value = 2,4 / 3,6 / 15 / 30	Max. inlet pressure 40 barg Outlet pressure 0,5-29 barg Kv-Value = 2,4 / 3,6 / 15 / 30	Max. inlet pressure 40 barg Outlet pressure 0,5-30 barg Kv-Value = 2,4 / 3,6 / 15 / 30	Max. inlet pressure 40 barg Outlet pressure 0,5-30 barg Kv-Value = 2,4 / 3,6 / 15 / 30	
		747LE/S-ES									
		757LE/S-ES									
	76LE/S-ES										
Manifold pressure regulator		ADR 75	Dome pressure regulator; 2,5 barg version available	Max. inlet pressure 25 barg Outlet pressure 0-1,5 barg (2,5 barg) Max. flow 75 m³/h							
		ADR 150	2 barg version available	Max. inlet pressure 25 barg Outlet pressure 0-1,5 barg (2 barg) Max. flow 150 m³/h							
		ADR 150 F	Spring loaded pressure regulator	Max. inlet pressure 25 barg Outlet pressure 0-1,5 barg Max. flow 150 m³/h							

**HIGH PRESSURE PIPING
ON CUSTOMER REQUEST**



**MAXIMUM PRECISION AND
CONSISTENCY FOR YOUR GAS
PRESSURE**



Material		Model	Remarks	Gases / Max. working pressures							Connection
				Opening pressure	Acetylene (A)	Oxygen (O ₂)	LPG (P)	Hydrogen (H ₂)	Natural Gas (M)	Nitrogen (N ₂)	
Brass		NV300		4 mbarg		16 barg	16 barg	16 barg	16 barg	16 barg	G 1-G 1.1/4
		ULTRA 30		5 mbarg		20 barg	20 barg	20 barg	20 barg	20 barg	G 1.1/2 1.1/2" NPT
		ULTRA 32	free combination of materials for housing (brass, stainless steel, aluminum) and seal(NBR/CR, FPM/FKM, EPDM/FFKM)	5 mbarg	1,5 barg	20 barg	20 barg	20 barg	20 barg	20 barg	G 1.1/2 1.1/2" NPT
		NV 400		4 mbarg		16 barg	16 barg	16 barg	16 barg	16 barg	G 1-G 1.1/4
		NV 400 intermediate flange		4 mbarg		16 barg	16 barg	16 barg	16 barg	16 barg	DN 40/50
		ULTRA 40		5 mbarg		20 barg	20 barg	20 barg	20 barg	20 barg	G 2.1/2 2.1/2" NPT
		ULTRA 42	free combination of materials for housing (brass, stainless steel, aluminum) and seal (NBR/CR, FPM/FKM,EPDM/FFKM)	5 mbarg		20 barg	20 barg	20 barg	20 barg	20 barg	G 2.1/2 2.1/2" NPT

ULTRA PERFORMANCE NOW AS STANDARD






Material		Model	Remarks	Gases / Max. working pressures							Connection
				Opening pressure	Acetylene (A)	Oxygen (O ₂)	LPG (P)	Hydrogen (H ₂)	Natural Gas (M)	Nitrogen (N ₂)	
Stainless steel		NV300-ES		4 mbarg		16 barg	16 barg	16 barg	16 barg	16 barg	G 1-G 1.1/4
		ULTRA 30		5 mbarg		20 barg	20 barg	20 barg	20 barg	20 barg	G 1.1/2 1.1/2" NPT
		ULTRA 32	free combination of materials for housing (brass, stainless steel, aluminum) and seal (NBR/CR, FPM/FKM, EPDM/FFKM)	5 mbarg	1,5 barg	20 barg	20 barg	20 barg	20 barg	20 barg	G 1.1/2 1.1/2" NPT
		NV 400-ES		4 mbarg			16 barg	16 barg	16 barg	16 barg	G 1.1/2-G 2
		ULTRA 40		5 mbarg		20 barg	20 barg	20 barg	20 barg	20 barg	G 2.1/2 2.1/2" NPT
		ULTRA 42	free combination of materials for housing (brass, stainless steel, aluminum) and seal (NBR/CR, FPM/FKM, EPDM/FFKM)	5 mbarg		20 barg	20 barg	20 barg	20 barg	20 barg	G 2.1/2 2.1/2" NPT
		800-ES		1 barg		240 barg		300 barg		300 barg	1/4" NPT

**A SAFE GAS SUPPLY WITH
NON RETURN VALVES**






Material		Model	Remarks	Technical information				Features			
				Opening pressure	Inlet-connection	Outlet-connection	With condensation outlet	Inlet filter (optional)	Manual ventilation	Manufactured and certified according to EN ISO 4126-1 AD 2000 bulletin AZ and VdTUV-bulletin 100	Single certification (Modul F)
Brass		SV 805	CE-marked according to PED 2014/68/EU CE0045	0,5 barg-45 barg	G 1/4-G 3/4 1/4" NPT-3/4" NPT	M24 x 1	X			X	X
		SV 805A	CE-marked according to PED 2014/68/EU CE0045 with venting adapter	0,5 barg-45 barg	G 1/4-G 3/4 1/4" NPT-3/4" NPT	1/2" NPT			X	X	X
		SV 805 SMART	CE-marked according to PED 2014/68/EU CE0045	0,5 barg-45 barg	G 1/4-G 3/4 1/4" NPT-3/4" NPT	1/2" NPT			X	X	X
		AV 319		10 mbarg-80 mbarg	G 1/8	G 1/8					X (optional)
		AV 619		5 mbarg-<500 mbarg	G 1/2-G 1	G 1/2-G 1	X	X		X	X (optional)
Stainless steel		SV 805-ES	CE-marked according to PED 2014/68/EU CE0045	0,5 barg-45 barg	G 1/4-G 3/4 1/4" NPT-3/4" NPT	M24 x 1	X			X	X
		SV 805A-ES	CE-marked according to PED 2014/68/EU CE0045 with venting adapter	0,5 barg-45 barg	G 1/4-G 3/4 1/4" NPT-3/4" NPT	1/2" NPT			X	X	X
		SV 805-ES SMART	CE-marked according to PED 2014/68/EU CE0045	0,5 barg-45 barg	G 1/4-G 3/4 1/4" NPT-3/4" NPT	1/2" NPT	X			X	X
		319-ES		10 mbarg-80 mbarg	G 1/2-G 1	G 1/2-G 1		X			X (optional)

Material	Image	Model	Remarks	Technical information				Features		
				Opening pressure	Inlet-connection	Outlet-connection	With condensation outlet	Inlet filter (optional)	Manual ventilation	Manufactured and certified according to EN ISO 4126-1 AD 2000 bulletin A2 and VdTUV-bulletin 100
Stainless steel		AV 619-ES		5 mbarg- < 500 mbarg	G 1/2- G 1	G 1/2- G 1		X		X
		AV919-ES		5 mbarg- < 500 mbarg	G 2	G 2				X
Aluminium anodized		AV 919		5 mbarg- < 500 mbarg	G 2	G 2				X

THE MOST EFFECTIVE PROTECTION AGAINST OVERPRESSURE



Application	Image	Model	Remarks	Gases / Max. working pressures / Flows					
				Acetylene (A)	Oxygen (O ₂)	LP6 (P)	Hydrogen (H ₂)	Natural Gas (M)	Carbon dioxide (CO ₂)
Gas Filter outlet points		622	fineness 40 micrometer	1,5 barg / 62 m ³ /h	16 barg	16 barg	16 barg	16 barg	
Gas Filter for pipelines		77 with brass-elements	Bronze filter element, fineness 5 or 50 micrometer, condensate drain		40 barg	50 barg	50 barg	50 barg	25 barg
		77	Nickel chromium filter element, fineness 0,5, 7-10 or 40 micrometer	1,5 barg / 312 m ³ /h	30 barg	50 barg	50 barg	50 barg	25 barg
		625	Condensat outlet fineness 40 micrometer	1,5 barg / 458 m ³ /h	10 barg	25 barg	25 barg	25 barg	
Stainless steel		HD Gas Filter	Nickel chromium filter element, fineness 30 or 80 micrometer	25 barg	50 barg	300 barg	300 barg	300 barg	100 barg
		LE6	Bronze filter element, fineness 15 micrometer		30 barg	40 barg	40 barg	40 barg	25 barg

		For all technical gases					
Model	Remarks	Minimum inlet pressure	Maximum inlet pressure	Maximum flow capacity	Mixing range	Mixing precision	
 <p>WITT KM 100</p>	For 2 or 3 Gases. Option: mounted on buffer tank	2 barg	20 barg	43 m ³ /h	0-100 %	better +/- 1% abs.	
 <p>WITT MG 50 - MG 500</p>	For 2 or 3 Gases. Option: mounted on buffer tank	3 barg	20 barg	100 m ³ /h- 940 m ³ /h	0-25 % or 0-100 %	better +/- 1% abs.	
 <p>WITT</p>							

OUR PRODUCT RANGE

GAS CONTROL EQUIPMENT

- Gas mixing systems
- Gas metering systems
- Gas analysers
- Leak detection systems
- Gas pressure vessels
- Engineering of customised systems

GAS SAFETY EQUIPMENT

- Flashback arrestors
- Non-return valves / check valves
- Quick couplers
- Safety relief valves
- Stainless steel devices
- Gas filters
- Pressure regulators
- Outlet points
- Lance holders
- Ball valves
- Automatic hose reels
- Test equipment
- Accessories
- Customised safety equipment

WITT-Gasetechnik GmbH & Co KG

Salinger Feld 4-8
58454 Witten
Deutschland
Tel. +49 (0)2302 8901-0
www.wittgas.com
witt@wittgas.com

GUSTUS & PARTNER GmbH

Installation – Service – Wartung
Alt Salbke 6-10, Geb. 59
39122 Magdeburg
Deutschland
Tel. +49 (0)391 4015246
gustus@wittgas.com

WITT Tecnología de Gas, S.L.

C/Simón Cabarga N° 2a – Bajo
39005 Santander
España
Tel. +34 942 835142
witt-espana@wittgas.com

WITT FRANCE S.A.R.L.

131 Voie de Compiègne
91390 Morsang sur Orge
France
Tel. +33 (0)160 151779
witt-france@wittgas.com

WITT Gas Techniques Ltd.

Unit 7 Burtonwood Industrial Estate
Phipps Lane, Burtonwood
Warrington, Cheshire
WA5 4HX
Great Britain
Tel. +44 (0)1925 234466
witt-uk@wittgas.com

WITT GAS INDIA PVT.LTD.

855/N, Upen Banerjee Road
Kolkata 700060
West Bengal
India
Tel. +91 9831319810
witt-india@wittgas.com

WITT ITALIA Srl.

Via Giovanni XXIII, 18
24030 Solza (BG)
Italia
Tel. +39 035 4933273
witt-italia@wittgas.com

WITT POLSKA Sp. z o. o.

Ul. Bulwar Dedala 16a
54-130 Wrocław
Poland
Tel. +48 71-352 28 56
witt-polska@wittgas.com

WITT Gas Controls LP

1055 Windward Ridge Parkway
Suite 170
Alpharetta, Georgia 30005
USA
Tel. +1 770 664 4447
witt-usa@wittgas.com