

## ACCESSORIES OXYBABY®

### for canisters, bottles, cans and mini packages



#### OXYBABY® Can-Piercer

The OXYBABY® Can-Piercer is essential for head space analysis of canisters, bottles and cans.

Safe interlocking and easy handling guarantees optimal quality controls also for canisters, bottles and cans with metal or plastic caps.

The Can-Piercer can be adjusted up to 405 mm maximum canisters, bottles - or cans height. The integrated needle protection and robust needles prevents needle breakage.

Material: steel

Weight: 7,5 kg (without OXYBABY®)

Dimensions (HxWxD): 585 x 155 x 235 mm (packed, without OXYBABY®)

Suitable for OXYBABY® M+ and OXYBABY® 6.0.



#### OXYBABY® Aquacheck

OXYBABY® Aquacheck is ideal for mini packages lower 2 ml sample gas volume.

The gas volume from two or more packages is collected in the water and analysable by the OXYBABY®.

Material: stainless steel

The OXYBABY® Aquacheck is available with and without water container.

Suitable for OXYBABY® M+ and OXYBABY® 6.0.

**Other models, options and accessories available upon request.**

# ACCESSORIES OXYBABY®

for canisters, bottles, cans and mini packages



## Can-Piercer: Application in practice

Order-No.	Needle length in mm	Hight of canisters, bottles, cans	Bottle holder	Overpressure	Gauge 0 - 6 bar	Conversion possible	Application	Device
590000156	5.5 mm	270 mm		x <1 bar(g)		x	beverage cans (without gas /without overpressure), eg. juice	OXYBABY®
590000165	8.5 mm	270 mm	x	x >1 bar(g)		x	bottles, bevarage cans (with gas / with overpressure), eg. Cola, mineral water	OXYBABY®
590000166	8.5 mm	390 mm	x	x >1 bar(g)		x	bottles, beverage cans (with gas / with overpressure), eg. Cola, mineral water	OXYBABY®
590000325	18.5 mm	390 mm	x	x >1 bar(g)		x	bottles, beverage cans (with gas / with overpressure), eg. Cola, mineral water	OXYBABY®
590000341	5.5 mm	390 mm	x	0 - 4 bar	x	x	bottles, beverage cans	no OXYBABY® connection, only pressure measurement
590000900	18.5 mm	405 mm	x	x <1 bar(g)		x	canisters (without gas /without overpressure), eg. oil	OXYBABY®

\*to prevent the OXYBABY® from damage by too high overpressure, too high flow rate, the calibration module has to be connected between calibration gas / zero gas and OXYBABY®.

To obtain clear results we adjust a pressure of 0.5 bar and a flow rate of approx. 100 ml/min.

### Attention:

The correct model of the required Can-Piercer type is dependent on

- the kind of liquid to be analysed,
- the available overpressure in the bottles / cans,
- the volume of the available headspace of the bottles / cans,
- the thickness of the caps / can walls

### Our recommendations:

Case	Application	Example	Recommendation
1	for beverages containing gas	cola, mineral water, lemonades, beer, etc.	590000165, 590000166 or 590000325
2	for beverages, free of gas	juices, wine, water mixtures, etc.	590000156, 590000900
3	for sole pressure measurement	from a can or bottle	590000341

### Retrofit components and spare parts:

Bottle holder	956721800
Canister holder	966169600
Tubular extension for CAN-Piercer	802128600
Tubular extension for CAN-Piercer (canister)	802826900
Can-Piercer holder (needle 18.5 mm)	956864800
Can-Piercer holder (needle 18.5 mm) (canister)	966169500
Can-Piercer holder (needle 8.5 mm)	956722000
Can-Piercer holder (needle 5.5 mm)	956674900
Can-Piercer holder (pressure measurement)	956883600
Needle connection with filter and RV	956721700
Hose	800707500
Luer-Lock connection female	800420800