

INLET PRESSURE MONITORING with alarm module AM3



Separate inlet pressure monitoring, also integrated available. A gas inlet pressure controlling for a variety of industrial applications.

A permanent inlet pressure monitoring to guarantee quality and productivity of production processes.

One of the advanced solutions for monitoring gas inlet pressures in gas mixing systems. The unit controls the gas pressures at the inlets of the gas mixer and in the receiver, ensures a constant quality process.



Benefits

- simultaneous monitoring up to 5 gas pressures
- easy-to-read TFT display, which activates automatically when approached
- device parameters (e.g. alarm limit values) can be easily set using capacitive keys
- graphic menu navigation is clear and intuitive
- different user levels
- permanent display of measured pressures
- high process reliability
- error messages or exceeds of threshold limits triggers an alarm and switches a potential free contact (e.g. to shut down machinery to avoid quality problems)
- data transfer via USB type B port
- continuous monitoring of freely adjustable limit values
- different international units (Bar, PSI, kPa and till 10 Bar in mBar possible) can be selected



Options

- for flammable gases available as Ex-version in separate control cabinet
- as a stand-alone unit with a separate housing
- data cable

Other models, options and accessories available upon request.

Please identify the individual gases at the time of enquiring!



INLET PRESSURE MONITORING

with alarm module AM3



| | |
|---|--|
| Type | separate as Stand-Alone-Unit or in WITT gas mixer integrated inlet pressure monitoring with alarm module AM3 |
| Gases | all technical gases (excluding toxic or corrosive gases, also no mixtures of fuel gases with gases including O ₂ for example air ...) |
| Temperature | -10 °C – +50 °C / +14 °F – +122 °F (operation) -20 °C – +60 °C / -4 °F – +140 °F (storage) |
| Explosion protection ATEX (option) | zone 1, II 2G IIB+H ₂ T3 |
| Gas connections for fuel gases | G 1/4 RH with cone, WITTFIX 6 mm G 3/8 LH with cone, WITTFIX 6 mm other connections available on request |
| Adjustable alarm range | min. 0 up to max. 200 barÜ (dependent to the individual sensor) |
| Input signal | 5 x 4 till 20 mA |
| Output signal | 5 x 4 till 20 mA mirrored to inlet |
| Load of potential-free contact | 250 V AC 5A or 24 V DC 2 A |
| Alarm signals | - 1 relay 230V SSR (solid state relay) or 24V SSR for frequent switching cycles and long lifetime - 2 potential-free changeover relays for switching external units in case of alarm limits and fault |
| Interfaces | USB type B port |
| Function keys | acknowledgement of alarm by resistive display setting by 4 capacitive keys |
| Display | - TFT display for setting parameters and alarm 1-8 - additional digital view of menu items - 4 bicolored LEDs for operating status, system fault, alarms 1-8 |
| Languages | German, English (more to follow) |
| Housing AM3 | plastic, IP 50 |
| Stand-Alone-Unit wall housing | stainless steel, splash proof plastic, IP 65 |
| Weight AM3 | 195 g |
| Stand-Alone-Unit wall housing | approx. 5.5 kg approx. 5.0 kg |
| Dimensions (HxWxD) AM3 | approx. 72 x 72 x 99 mm (2.83 x 2.83 x 3.90 inches) (without connections) |
| Stand-Alone-Unit wall housing | approx. 172 x 242 x 278 mm (6.77 x 9.53 x 10.94 inches) (without connections) approx. 280 x 302 x 158 mm (11.02 x 11.89 x 6.22 inches) (without connections) |
| Voltage | 230 V AC, 110 V AC or 24 V DC |
| Approvals | Company certified according to ISO 9001 CE-marked according to: - EMC 2014/30/EU - Low Voltage Directive 2014/35/EU - ATEX 114 Directive 2014/34/EU |