

## CONTROL UNIT PLUS for LEAK-MASTER® EASY



Controller for leak detector LEAK-MASTER® EASY. In combination with LEAK-MASTER® EASY features non-destructive detection of the smallest leaks without the need of costly helium.

Pre-defined measurement programmes, an altitude simulation as well as an user independently quick and continuously working mode characterise this device.



Easily connected to your LEAK-MASTER® EASY.

A flexible controller to guarantee quality and productivity of production processes.

### Benefits

- minimal response time
- quick product change
- no calibration required
- simple to operate via touch-screen
- easy installation and start-up
- permanent monitoring of set limit values
- operator friendly – data and process parameter entry and administration by means of integrated keyboard or remote personal computer (e.g. MS-Excel®)
- perfect documentation by complete user- and product data as well as error logs
- data transmission of results as a CSV file and PDF report via Ethernet (browser-based EASY PLUS control software) or via USB stick
- Ethernet connection for network integration
- measured data storage
- administration of product names
- user management for measurement personalization
- individual configurable error codes with identification from type and location of leak

- ideal for altitude simulation testing
- for retrofitting your existing LEAK-MASTER® EASY
- hygienic and easy to clean splash-proof stainless steel cabinet / housing

### Options

- Barcode Reader for simple and quick user/product selection with IP-protection

**Other models, options and accessories available upon request.**

# CONTROL UNIT PLUS

## for LEAK-MASTER® EASY



<b>Type</b>	Control Unit PLUS for LEAK-MASTER® EASY
<b>Vacuum</b>	max. 11.6 psi
<b>Temperature (gas/environment)</b>	32°F up to +104°F
<b>Interfaces</b>	Ethernet (optional WLAN) USB by memory stick for software Update RS 232 with ASCII-output of date, time, measured value RJ45 Ethernet FTP-Server for profiles, product and user data, software Update analog output 4-20 mA or 0-10 V
<b>Housing</b>	stainless steel, IP 43
<b>Weight</b>	approx. 18 lb
<b>Dimensions (HxWxD) with carry handle</b>	approx. 4.3 x 11.8 x 10.2 inches
<b>Voltage</b>	100 – 240 V AC; 50 – 60 Hz
<b>Power consumption</b>	230 V AC / 0.12 A
<b>Approvals</b>	Company certified according to ISO 9001 and ISO 22000 CE marked according to: - EMC 2014/30/EU - Low Voltage Directive 2014/35/EU for food-grade gases according to: - Regulation (EC) No 1935/2004